



STANDARD BLIND RIVET OPEN TYPE A2/A2 5,0X25,0 MM,
 DOMED HEAD,
 GRIPRANGE 16,0-21,0 MM,
 DRILLING HOLE 5,1 MM

| DIMENSIONS | mm | ISO |
|------------------|--------------------------------|------------|
| L | 25,0 +1,0/-0,2 | 14589:2000 |
| Fmax | 30,4 | 14589:2000 |
| D1 | 5,0 +0,08/-0,15 | 14589:2000 |
| D2 | 9,5 +0/-1,0 | 14589:2000 |
| k | 1,1 +/-0,3 | 14589:2000 |
| P | >=27,0 | 14589:2000 |
| d | 2,9 | 14589:2000 |
| SHEARING FORCE | 5000 N | 14589:2000 |
| TENSILE FORCE | 6500 N | 14589:2000 |
| BODY MATERIAL | STAINLESS STEEL A2 AISI 304 | |
| MANDREL MATERIAL | STAINLESS STEEL A2 AISI 304 | |

| | | | | | |
|-------------------|--------------------|--|----------------------------|--------------------|-------------------|
| customer Nr.: | production Nr.: | Tolerances according to 14589:2000, Acceptance inspection according to ISO 3269 | | | |
| drawn C. Bakar | checked S. Köhr | approved by - date M. Goebel | Name of file 7030150250 | date 2021/04/26 | scale no scale |
| GOEBEL GMBH | | | 7030150250 | | |
| | | | 2116 | DRAWING Nr.: | Version REV0 |