



| | | | |
|--|-------------|---------------------|-------------------------------|
| PAN HEAD SELF DRILLING SCREW 4,2x16,0mm, WITH SQUARE SOCKET AND SLOT, FURNACE HEAT TREATMENT, HARDENED DRILLING POINT #2, STAINLESS STEEL, SILVER GL COATED | | | |
| A | 8,00 - 8,30 | p | 1,31 - 1,51 |
| M | 1,95 - 2,25 | d | 3,10 - 3,30 |
| n | 1,30 - 1,50 | U | 5,00 - 6,00 |
| Q | 1,75 - 2,05 | R | 3,35 - 3,45 |
| t | 1,10 - 1,50 | D | 4,08 - 4,21 |
| k | 2,75 - 3,05 | L | 15,10 - 16,90 |
| MECHANICAL PROPERTIES | | | |
| MATERIAL | AISI 302HQ | DRILLING CAPABILITY | 2x0,8mm STAINLESS STEEL |

customer Nr.: production Nr.: Tolerances according to ISO 4759-1, all dimensions in mm, Acceptance inspection according to ISO 3269

designed C. Bakar checked S. Köhr approved by - date M. Goebel Name of file 6661042160 date 2021/08/31 scale no scale

GOEBEL GMBH

6661042160

2132

DRAWING Nr.:

Version
REV0

paper
1/1