

Linsenkopf-Bohrschrauben (SQ)



mit Innenvierkant

Pan head self drilling screws (SQ)

with square socket in head

Vis autoforeuse-tête cylindrique bombée (SQ)

empreinte carrée



- ① C1 W.-Nr. 1.4006 AISI 410 **GOEBEL silber GL**
 C1 W.-Nr. 1.4006 AISI 410 **GOEBEL silver GL**
 C1 W.-Nr. 1.4006 AISI 410 **GOEBEL GL argenté**

Ø 4,2 mm

M = No. 2

= C

A2/A4	Stahl Steel Acier		Lg min			
2 x 0,8 mm	max. 3,0 mm	4,2 x 13 mm	4,3 mm	2	1000	41631 42 130
2 x 0,8 mm	max. 3,0 mm	4,2 x 16 mm	7,3 mm	2	1000	41631 42 160
2 x 0,8 mm	max. 3,0 mm	4,2 x 19 mm	10,3 mm	2	1000	41631 42 190

UPM / RPM / TR-MN = max. 1200



Ø 4,8 mm

M = No. 2

= C

A2/A4	Stahl Steel Acier		Lg min			
2 x 1,0 mm	max. 4,4 mm	4,8 x 13 mm	3,7 mm	2	1000	41631 48 130
2 x 1,0 mm	max. 4,4 mm	4,8 x 16 mm	5,8 mm	2	1000	42631 48 160
2 x 1,0 mm	max. 4,4 mm	4,8 x 19 mm	8,7 mm	2	1000	42631 48 190

UPM / RPM / TR-MN = max. 1200



- ① C1 W.-Nr. 1.4006 AISI 410 **GOEBEL silber GL**
 C1 W.-Nr. 1.4006 AISI 410 **GOEBEL silver GL**
 C1 W.-Nr. 1.4006 AISI 410 **GOEBEL GL argenté**
- ② Polyamid
 Polyamide
 Polyamide

Ø 4,2 mm

M = No. 2

P = 2,0 mm

D = 12,0 mm

= C

A2/A4	Stahl Steel Acier		Lg min			
2 x 0,8 mm	max. 3,0 mm	4,2 x 13 mm	3,3 mm	2	1000	41641 42 130
2 x 0,8 mm	max. 3,0 mm	4,2 x 16 mm	6,3 mm	2	500	41641 42 160
2 x 0,8 mm	max. 3,0 mm	4,2 x 19 mm	9,3 mm	2	500	41641 42 190

UPM / RPM / TR-MN = max. 1200

Ø 4,8 mm

M = No. 2

P = 2,0 mm

D = 12,0 mm

= C

A2/A4	Stahl Steel Acier		Lg min			
2 x 1,0 mm	max. 4,4 mm	4,8 x 16 mm	2,7 mm	2	500	41641 48 160
2 x 1,0 mm	max. 4,4 mm	4,8 x 19 mm	4,8 mm	2	500	41641 48 190
2 x 1,0 mm	max. 4,4 mm	4,8 x 25 mm	7,7 mm	2	500	41641 48 250

UPM / RPM / TR-MN = max. 1200