

DIN 7504 SQ

LINSENKOPF-BOHRSCRAUBEN (SQ)

MIT INNENVIERKANT

PAN HEAD SELF DRILLING SCREWS (SQ)

WITH SQUARE SOCKET IN HEAD

VIS AUTOFOREUSE-TÊTE CYLINDRIQUE BOMBÉE (SQ)

EMPREINTE CARRÉE



Inklusive
including
inclusive



C1 W.-Nr. 1.4006 AISI 410 GOEBEL silber GL C1 W.-Nr. 1.4006 AISI 410 GOEBEL silver GL C1 W.-Nr. 1.4006 AISI 410 GOEBEL GL argenté	Polyamid Polyamide Polyamide	EPDM / A2 W.-Nr. 1.4301/03 AISI 305 EPDM / A2 W.-Nr. 1.4301/03 AISI 305 EPDM / A2 W.-Nr. 1.4301/03 AISI 305	

Ø 4,2 mm		4.2 mm diameter screws				4.8 mm diameter screws				4.2 mm diameter screws				
		LG min		CODE	P	D	LG min		CODE	P	D	LG min		CODE
4,2 x 13 mm		4,3 mm	1000	41631 42130	2,0 mm	12,0 mm	3,3 mm	1000	41641 42130	3,0 mm	12,0 mm	2,8 mm	500	41624 42130
4,2 x 16 mm		7,3 mm	1000	41631 42160	2,0 mm	12,0 mm	6,3 mm	500	41641 42160	3,0 mm	12,0 mm	5,8 mm	500	41624 42160
4,2 x 19 mm		10,3 mm	1000	41631 42190	2,0 mm	12,0 mm	9,3 mm	500	41641 42190	3,0 mm	12,0 mm	8,8 mm	500	41624 42190

UPM/RPM/TR-MIN = max. 1200

Ø 4,8 mm

M = No. 2

= C

UPM/RPM/TR-MIN = max. 1200

4.8 mm diameter screws	4.8 mm diameter screws				4.2 mm diameter screws								
4,8 x 13 mm	3,7 mm	1000	41631 48130	P	D	LG min		CODE	P	D	LG min		CODE
4,8 x 13 mm	3,7 mm	1000	41631 48130						3,0 mm	12,0 mm	2,2 mm	500	41624 48130
4,8 x 16 mm	5,8 mm	1000	42631 48160	2,0 mm	12,0 mm	4,8 mm	500	41641 48160	3,0 mm	12,0 mm	4,3 mm	500	41624 48160
4,8 x 19 mm	8,7 mm	1000	42631 48190	2,0 mm	12,0 mm	7,7 mm	500	41641 48190	3,0 mm	12,0 mm	7,2 mm	500	41624 48190
4,8 x 25 mm				2,0 mm	12,0 mm	13,7 mm	500	41641 48250					

4.2 mm diameter screws	4.8 mm diameter screws	Stahl Steel Acier
4,2 x 13 mm	2 x 0,8 mm	max. 3,0 mm
4,2 x 16 mm	2 x 0,8 mm	max. 3,0 mm
4,2 x 19 mm	2 x 0,8 mm	max. 3,0 mm
4,8 x 13 mm	2 x 1,0 mm	max. 4,4 mm
4,8 x 16 mm	2 x 1,0 mm	max. 4,4 mm
4,8 x 19 mm	2 x 1,0 mm	max. 4,4 mm
4,8 x 25 mm	2 x 1,0 mm	max. 4,4 mm

Änderungen vorbehalten Subject to modifications Sous réserve de modifications